

3300KVA RESISTIVE-REACTIVE 690V LOADBANK

Applied V	400V	440V	480V	600V	690V
kW	887	1074	1278	1996	2640
App. kVA 50Hz	1109	1342	1597	2495	3300
Power Factor	0.8	0.8	0.8	0.8	0.8
App. kVA 60Hz	1046	1266	1506	2354	3113
Power Factor	0.85	0.85	0.85	0.85	0.85



Advertised Specifications and Features

- Transportable 10ft ISO style type loadbank
- HHT100 Remote Controller or Eclipse software via PC
- 1.66kW / 1.96kVAr Minimum load step resolution
- 50Hz or 60Hz operation
- Power factor 0.8 - 1.0pf
- Available for immediate delivery

*Photo for illustration purposes only

For further information contact:

Crestchic Limited
Third Avenue, Centrum 100
Burton-on-Trent, DE14 2WF
United Kingdom

Tel +44 (0) 1283 531645
Fax +44 (0) 1283 510103
sales@crestchic.com
www.crestchicloadbanks.com

The information given in this literature is, to the best of our knowledge, correct at the time of going to print. However, Crestchic is constantly looking at ways of improving their products and services and therefore reserve the right to change, without prior notice, any of the data contained in this publication. Any orders placed will be subject to our Standard Conditions of Sale, available on request. **Crestchic is part of the NBI group of companies.**